

Introduction to ADTs

Abstract Data Types

CS 3358
Summer II 2013

Jill Seaman

No corresponding sections from the textbook

1

Data Structure

- A particular way of storing and organizing data in a computer so that it can be used efficiently

*from wikipedia

- A data type having
 - a specific, physical representation of the data
 - operations over its data
- A concrete description
- defined in terms of how it is implemented
 - implementation-dependent

2

Abstract Data Type

- A set of data values and associated operations that are precisely specified independent of any particular implementation.

*from <http://xlinux.nist.gov/dads/>

- A data type having
 - a logical representation of the data
 - operations over its data
- A logical description
- may be implemented in various ways
 - implementation-independent

3

Data Structures again

- The term “data structures” is often extended to include both concrete AND logical descriptions of complicated data types.
- A list of data structures could include ADTs
 - arrays
 - linked lists
 - stacks
 - queues
 - vectors or lists

Which are concrete?
Which are abstract?

4

Commonly used ADTs

- The purpose of many commonly used ADTs is to:
 - store a collection of objects
 - potentially organize the objects in a specific way
 - provide potentially limited access to the objects
- These ADTs are often called
 - containers
 - collections
 - container classes

5

Commonly used ADTs

- Examples:
 - List (or sequence or vector)
 - Set
 - Multi-set (or bag)
 - Stack and Queue
 - Tree
 - Map (or dictionary)

Stacks, Queues, and Trees will be covered later in the semester

6

A List ADT

- **Values:** ordered (1st, 2nd, etc) set of objects
- **Operations** often include:
 - constructor: creates an empty list
 - isEmpty: is the list empty
 - size: returns the number of elements
 - add(i,e): inserts an element e at position i
 - remove(i): removes the element at position i
 - get(i): returns the element at position i
 - set(i,e) changes the element at position i to value e

7

A Set ADT

- **Values:** unordered collection of unique objects
- **Operations** often include:
 - constructor: creates an empty set
 - isEmpty: is the set empty
 - size: returns the number of elements
 - add(e): adds an element to the set (if not there)
 - remove(e): removes an element from the set (if it is there)
 - contains(x): true if x is in the set
 - addAll(s): adds all elements from set s to this one (union)

A Bag (multi-set) ADT

- **Values:** unordered collection of objects (may include duplicates)
- **Operations** may include:
 - constructor: creates an empty bag
 - isEmpty: is the bag empty
 - size: returns the number of elements
 - add(e): adds an element e to the bag
 - remove(e): removes one copy of an element from the bag (if it has any)
 - removeAll(e): removes all copies of e from the bag
 - occurrences(x): how many times x is in the bag

A Map ADT

- **Values:** a collection of unique keys and a collection of values where each key is associated with a single value. Keys have one type, values another.
- **Operations** may include:
 - constructor: creates an empty map
 - isEmpty: returns true if map has no key-value pairs
 - size: returns the number of key-value pairs in the map
 - get(k): returns value associated with key k (if any)
 - put(k,v): associates value v with key k (adds a pair)
 - keySet: returns a set of all the keys in the map

10

Implementing an ADT

- **Interface (*.h):**
 - class declaration
 - prototypes for the operations (interface)
 - data members for the actual (concrete) representation
- **Implementation (*.cpp)**
 - function definitions for the operations
 - depends on representation of data members (their concrete implementation)

11

Example ADT: bag version 1

```
bag.h
class Bag
{
public:
    Bag ();
    void add(int element);
    void remove(int element);
    int occurrences(int element) const;
    bool isEmpty() const;
    int size() const;
    static const int CAPACITY = 20;
private:
    int data[CAPACITY];
    int count;
};
```

true interface: prototypes are independent of the implementation

concrete representation, implementation dependent

what is the difference between count and CAPACITY?

12

Example ADT: bag version 1

bag.cpp

```
#include "bag.h"
#include <cassert>
using namespace std;

Bag::Bag () {
    count = 0;
}
void Bag::add(int element) {
    assert (count < CAPACITY); ← what does this do?
    data[count] = element;
    count++;
}
void Bag::remove(int element) {
    int index = -1; //change to position if found
    for (int i=0; i<count && index==-1; i++) {
        if (data[i]==element) {
            index = i;
        }
    }
    if (index!=-1) { //found, replace w/ last elem
        data[index] = data[count-1];
        count--;
    }
}
//continued...

```

13

Example ADT: bag version 1

bag.cpp, cont.

```
int Bag::occurrences(int element) const {
    int occurrences=0;
    for (int i=0; i<count; i++) {
        if (data[i]==element) {
            occurrences++;
        }
    }
    return occurrences;
}
bool Bag::isEmpty() const {
    return (count==0);
}
int Bag::size() const {
    return count;
}

```

14

bag "driver"

bagTest.cpp

```
#include<iostream>
#include "Bag.h"
using namespace std;

int main ()
{
    Bag b;

    b.add(4);
    b.add(8);
    b.add(4);

    cout << "size " << b.size() << endl;
    cout << "how many 4's: " << b.occurrences(4) << endl << endl;

    b.remove(4);
    cout << "removed a 4" << endl;
    cout << "size " << b.size() << endl;
    cout << "how many 4's: " << b.occurrences(4) << endl << endl;
}

```

15

bag "driver"

bagTest.cpp

```
Bag c(b);

cout << "copied to c" << endl;
cout << "size " << c.size() << endl;
cout << "how many 4's: " << c.occurrences(4) << endl << endl;

b.add(10);
cout << "added 10 to b" << endl;
cout << "b.size " << b.size() << endl;
cout << "c.size " << c.size() << endl << endl;

cout << "starting to add 20 items" << endl;
for (int i=0; i<20; i++)
    b.add(33);
cout << "added 20 more items to b" << endl;

return 0;
};

```

16

bag "driver": output

output of running bagTest

```
size 3
how many 4's: 2

removed a 4
size 2
how many 4's: 1

copied to c
size 2
how many 4's: 1

added 10 to b
b.size 3
c.size 2

starting to add 20 items
Assertion failed: (count < CAPACITY), function add, file
bag.cpp, line 12.
Abort trap: 6
```

17

Bag version 1 summary

- Implemented using a fixed size array
- When adding more elements than fit in the bag, the program exits.
- Solution:
 - use a dynamically allocated array
 - when its capacity is reached, allocate a new, bigger array.

18

bag version 2

bag.h

```
class Bag
{
public:
    Bag ();

    Bag(const Bag &);
    ~Bag();
    void operator=(const Bag &);

    void add(int element);
    void remove(int element);

    int occurrences(int element) const;
    bool isEmpty() const;
    int size() const;

    static const int INCREMENT = 20;

private:
    int *data; //pointer to bag array
    int capacity; //size of the array
    int count; //number of elements currently in array
};
```

"The big three"

concrete representation

bag version 2

bag.cpp

```
Bag::Bag () {
    count = 0;
    capacity = INCREMENT;
    data = new int[capacity];
}

//copy constructor
Bag::Bag(const Bag &rhs) {
    data = new int[rhs.capacity]; //allocate new array

    capacity = rhs.capacity; //copy values
    count = rhs.count;
    for (int i=0; i<count; i++) {
        data[i] = rhs.data[i];
    }
}

//desctructor
Bag::~Bag() {
    delete [] data;
}
```

20

bag version 2

bag.cpp, cont.

```
void Bag::operator=(const Bag &rhs) {
    if (data) delete [] data; //delete old array
    data = new int[rhs.capacity]; //allocate new array

    capacity = rhs.capacity; //copy values
    count = rhs.count;
    for (int i=0; i<count; i++) {
        data[i] = rhs.data[i];
    }
}

void Bag::add(int element) {
    //if count is at the capacity, resize
    if (count==capacity) {
        capacity += INCREMENT;
        int *newData = new int[capacity]; //new array
        for (int i=0; i<count; i++) { //copy values
            newData[i] = data[i];
        }
        delete [] data; //delete old array
        data = newData; //make data point to new
    }

    data[count] = element; //add new element
    count++;
}
```

no changes to remaining functions!

21

bag "driver": output version 2

output of running bagTest

```
size 3
how many 4's: 2

removed a 4
size 2
how many 4's: 1

copied to c
size 2
how many 4's: 1

added 10 to b
b.size 3
c.size 2

starting to add 20 items
added 20 more items into b
```

resizing succeeded!

22